









Equipment	Description	Price	Websites for ordering
 <p data-bbox="139 499 418 569">SGC Plus H₂S Monitor SGC-P-H</p>	<ul data-bbox="516 195 976 422" style="list-style-type: none"> • Shows months left on monitor until H₂S gas has been detected • Low alarm set at 10 ppm and high alarm set at 15 ppm • May last longer than 2 years if hibernated with IR-link accessory 	<p data-bbox="1016 195 1159 222">\$150-\$200</p>	<p data-bbox="1208 195 1549 296">baselineequipment.com gasdetectorshop.com Envirosafetyproducts.com</p>
 <p data-bbox="77 926 483 995">BW Clip Real Time H₂S Monitor BWC2R-H</p>	<ul data-bbox="516 583 976 926" style="list-style-type: none"> • Shows concentration of H₂S gas present • Lasts 2 years except when used with hibernation case then can last longer • Low alarm set at 10 ppm and high alarm set at 15 ppm • May last longer than 2 years if hibernated with hibernation case 	<p data-bbox="1016 583 1159 611">\$150-\$200</p>	<p data-bbox="1208 583 1419 646">Pksafety.com TEquipment.net</p>
 <p data-bbox="107 1430 451 1465">25 ppm H₂S calibration gas</p>	<ul data-bbox="516 1014 976 1472" style="list-style-type: none"> • H₂S gas will be balanced with air, methane, or nitrogen • Allow extra time for your order to be made (1 week) • Hazardous materials fee will be added to order (~\$85) • Different volumes of gas will be different prices • Used with regulator and can see when the cylinder is almost empty • Gas can be used for calibration of monitor as well as bump testing 	<p data-bbox="1016 1014 1143 1077">\$30-\$200 17L- 34L</p>	<p data-bbox="1208 1014 1430 1115">Pksafety.com Calgasdirect.com Grainger.com</p>
 <p data-bbox="99 1898 461 1969">10 liter H₂S gas 25 ppm with aerosol trigger</p>	<ul data-bbox="516 1518 976 1976" style="list-style-type: none"> • H₂S gas will be balanced with air, methane, or nitrogen • Allow extra time for your order to be made (1 week) • Hazardous materials fee will be added to order (~\$85) • Used with spare balloon assembly kit adaptor for bump gas • Cannot tell when cylinder is almost empty • Shorter shelf life than regular calibration gas 	<p data-bbox="1016 1518 1068 1545">\$30</p>	<p data-bbox="1208 1518 1430 1545">Calgasdirect.com</p>

 <p>Regulator with a flow rate of 0.5 liters per minute</p>	<ul style="list-style-type: none"> • Used with calibration gas • Needs to have a flow rate of 0.5 liters per minute • Will need tubing to connect top of regulator to calibration cap 	<p>\$105-\$160</p>	<p>Pksafety.com Grainger.com Calgasdirect.com</p>
 <p>Spare balloon assembly kit and adaptor for bump gas</p>	<ul style="list-style-type: none"> • Used with the 10 liter H₂S gas with aerosol trigger 	<p>\$15</p>	<p>TEquipment.net jjstech.com</p>
 <p>BW Clip Hibernation case</p>	<ul style="list-style-type: none"> • Can increase the life span of the BW Clip Realtime to over 2 years • Monitor must be in case for 2 weeks before time stops on the monitor • Store this and the monitor in an area with low hydrogen sulfide gas presence 	<p>\$15-26</p>	<p>Pksafety.com Grainger.com</p>
 <p>Gas Clip Technologies IR Link</p>	<ul style="list-style-type: none"> • Communication link for Gas Clip Devices • Used to reset alarm set points, download event logs and data • Works on PC computers 	<p>\$87-\$100</p>	<p>baselineequipment.com pksafety.com</p>